

LOW VIBRATION HEAVY DUTY SCABBLER - SINGLE HEAD

SH1



THE SH1 AND VL SH1 SINGLE HEAD SCABBLERS ARE THE IDEAL TOOLS FOR ROUGHING AND PREPARING CONCRETE IN SMALL AREAS SUCH AS CONCRETE JOINTS.

The VLSH1 low vibration model helps reducing the risk to operators of vibration related injuries.

The optional TVS[®] vacuum shroud allows the connection of an industrial dust collector for collecting nuisance and hazardous dust for protection of operators and environment.



Low vibration options available



Dust control options available

See page 72 for our full range of vacuums

FEATURES & BENEFITS

- Single replaceable tough carbide tipped piston for fast production and long service life
- Ergonomic handle for ease of use – Also available with a short handle for tight areas
- Simple and robust design for easy maintenance
- Optional Trelawny Vibro-LoTM vibration reduction system for operator safety

APPLICATIONS

- Removal of laitance
- Roughening and exposing aggregate
- Preparing joints and cracks
- Removing coatings
- Reduction and levelling



REDUCING LEVELS ON CONCRETE



ROUGHENING CONCRETE











CONCRETE PREPARATION

LOW VIBRATION HEAVY DUTY SCABBLER - SINGLE HEAD

SH1

KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description
	612.5320	Single Piece Cruciform Piston Flatter surface profile, ideal for fast reduction of material
	612.5325	Single Piece Bush Piston Rough pitted profile, ideal for application of fresh concrete or coatings
	614.5301	Brush Seal
	437.5100	Vacuum Shroud * Not available for low vibration models
	815.5550	Whip Check
	859.1530	1/4" BSP Inline lubricator
	421.3452	Whip Hose Consists of air hose 3/8 BSP claw - 2m
	458.1530	Whip Hose & Oiler Assembly Consists of whip hose, whip check and 1/4 Inline lubricator



TECHNICAL DATA

Model	Part Number	Weight (kg)	Length (mm)	Working Height (mm)	Blows Per Minute (BPM)	Air Consumption (lps - cfm)	Noise Level (db (A))	Vibration Level (Aeq m/s ²)
Single Scabbler Bush Hammer Head	151.5250	2.6	485	160	2400	3 - 6.5	94	7.0
Single Scabbler Cruciform Head	151.5200	2.6	485	160	2400	3 - 6.5	94	7.0
Low Vibration Single Scabbler Bush Hammer Head	196.5105	2.5	465	160	2900	5.6 - 11.9	91	4.5
Low Vibration Single Scabbler Cruciform Head	196.5100	2.5	465	160	2900	5.6 - 11.9	91	4.5
Single Scabbler Cruciform Head fitted with shroud	139.5192	2.6	485	160	2400	3 - 6.5	94	7.0

