

UT8892SP-3

AIRCRAFT DRILL MOTOR INTERNAL SPLINE TOOL

FEATURES

- Machined carbon fiber blades for lubrication free operation
- Highest precision engineering ensures 600,000 cycles of use
- Internal silencer baffle reduces noise pressure level to 75 dBA
- Precision needle bearings and gears and gear case interchangeable with leading brand
- Advanced ergonomic handle design with insulated coating for maximum operator comfort
- Ported throttle valve for precise variable speed control
- Internal spline drive for use with Universal Tool or Jiffy® "L"- Foot and Pancake Drilling Attachments
- Best for: Continuous precision air frame work

SPECIFICATIONS

Motor (HP)	0.45
Motor (kW)	0.33
Gear Ratio	6:1
Throttle Style	Ported
Speed (RPM)	3,300
Exhaust	Rear
Chuck (in.)	Internal Spline
Weight (lbs.)	1.05
Weight (kg.)	0.5
Length (in.)	6.25
Length (mm)	159
Rec. Pressure	90 psi-6.2 bar
Rec. Hose (I.D. in.)	3/8"
Air Cons. (cfm)	4
Air Inlet (in.)	1/4



Air Tools for Industry



UNIVERSAL TOOL

a Division of Florida Pneumatic Manufacturing Corporation 851 Jupiter Park Lane / Jupiter, Florida 33458 www.universaltoolsusa.com

(800) 356-3392